

# SpringBoot config

## application.properties

### H2

```
spring.datasource.url=jdbc:h2:file:./db/ecommerce;DB_CLOSE_ON_EXIT=FALSE
spring.datasource.username=sa
spring.datasource.password=
spring.datasource.driverClassName=org.h2.Driver
spring.jpa.hibernate.ddl-auto=update
spring.jpa.properties.hibernate.dialect=org.hibernate.dialect.H2Dialect

spring.h2.console.enabled=true
spring.h2.console.path=/h2-console

#Quote sur les identifiants dans la BDD
spring.jpa.properties.hibernate.globally_quoted_identifiers=true
```

### Logs JPA

```
#spring.jpa.show-sql=true
spring.jpa.properties.hibernate.format_sql=true
# logs the SQL statements
# basic log level for all messages
logging.level.org.hibernate=info
# SQL statements and parameters
logging.level.org.hibernate.SQL=debug
logging.level.org.hibernate.orm.jdbc.bind=trace
```

From:  
<http://slamwiki2.kobject.net/> - **SlamWiki 2.1**

Permanent link:  
[http://slamwiki2.kobject.net/eadi/bloc3/dev\\_av/config](http://slamwiki2.kobject.net/eadi/bloc3/dev_av/config)

Last update: **2025/09/17 16:00**

