Méthodes

render

```
render (name, options)
```

Affiche le contenu d'un template dans une zone outlet nommée, en passant éventuellement des paramètres (model, controller...)

```
// ...

Router.map(function() {
  this.route('photos');
});

export default Router;
```

```
<!-- application.hbs -->
<div class='something-in-the-app-hbs'>
  {{outlet "anOutletName"}}
</div>
```

Il est possible d'afficher **photos.hbs** dans l'outlet **“anOutletName”** du template **application.hbs** en appelant la méthode **render** :

```
import Ember from 'ember';

export default Ember.Route.extend({
  renderTemplate() {
    this.render('photos', {
      into: 'application',
      outlet: 'anOutletName'
    })
  }
});
```

La méthode **render** peut permettre également de préciser le controller et le model à utiliser :

```
import Ember from 'ember';

export default Ember.Route.extend({
  renderTemplate(controller, model){
```

```
    this.render('posts', {    // the template to render, referenced by name
      into: 'application',    // the template to render into, referenced by name
      outlet: 'anOutletName', // the outlet inside `options.into` to render into.
      controller: 'someControllerName', // the controller to use for this template,
referenced by name
      model: model            // the model to set on `options.controller`.
    })
  }
});
```

From:
http://slamwiki2.kobject.net/ - **SlamWiki 2.1**

Permanent link:
http://slamwiki2.kobject.net/richclient/emberjs/router/methods?rev=1516844057

Last update: **2019/08/31 14:38**