

# Composants client

Dès qu'on utilise :

- useState
- useEffect
- interaction utilisateur

Il faut un composant client et déclarer :

```
"use client"
```

Exemple :

```
"use client"

import { useState } from "react"

export default function Counter() {
  const [count, setCount] = useState(0)

  return (
    <div>
      <p>{count}</p>
      <button onClick={() => setCount(count + 1)}>+1</button>
    </div>
  )
}

<sxh>
===== Hooks de base =====

===== useState/useEffect =====
=== useState ===

<sxh ts;gutter:false>
const [value, setValue] = useState("")
```

## useEffect

```
useEffect(() => {
  console.log("monté")
}, [])
```

## useRouter (navigation)

```
"use client"
```

Last  
update: 2026/04/03 11:51 web:framework:nextjs:client-component <http://slamwiki2.kobject.net/web/framework/nextjs/client-component?rev=1775209865>

```
import { useRouter } from "next/navigation"  
  
const router = useRouter()  
  
router.push("/events")
```

### useParams (récupérer ID côté client)

```
import { useParams } from "next/navigation"  
  
const params = useParams()  
console.log(params.id)
```

From:  
<http://slamwiki2.kobject.net/> - **SlamWiki 2.1**

Permanent link:  
<http://slamwiki2.kobject.net/web/framework/nextjs/client-component?rev=1775209865>

Last update: **2026/04/03 11:51**

