

Next-auth

Permet de gérer l'authentification sur une application nextJS en utilisant différent Provider. A l'avantage d'utiliser la session nextJS.

Installation

```
npm install next-auth@beta @types/next-auth
```

Configuration

```
import NextAuth from "next-auth";
import CredentialsProvider from "next-auth/providers/credentials";
import HttpService from "@services/HttpService";
import API_URLS from "@constants/ApiUrls";
import { decodeJwt } from "jose";

interface AuthToken {
  accessToken: string;
  refreshToken: string;
  user: any;
}

async function refreshAccessToken(token: AuthToken) {
  try {
    const refreshedToken = await HttpService.post(API_URLS.refreshToken, {
      refreshToken: token.refreshToken,
    });

    if (!refreshedToken || !refreshedToken.accessToken) {
      throw new Error("Refresh token failed");
    }

    return {
      ...token,
      accessToken: refreshedToken.accessToken,
      accessTokenExpires: Date.now() + refreshedToken.expiresIn * 1000,
      refreshToken: refreshedToken.refreshToken ?? token.refreshToken,
    };
  } catch (error) {
    console.error("Erreur lors du rafraîchissement du token", error);
    return { ...token, error: "RefreshAccessTokenError" };
  }
}

// @ts-ignore
export const authConfig = {
```

```
pages: {
  signIn: '/login',
  signOut: "/logout",
},
providers: [
  CredentialsProvider({
    id: "credentials",
    name: "Credentials",
    credentials: {
      username: { label: "Login", type: "text" },
      password: { label: "Password", type: "password" },
    },
    async authorize(credentials) {
      const resp = await HttpService.post(API_URLS.authLogin, {
        username: credentials.username,
        password: credentials.password,
      });

      if (resp.ok) {
        throw new Error("Invalid credentials");
      }
      const token=resp.data;
      const user = decodeJwt(token.accessToken);

      return {
        id: user.sub,
        name: user.name,
        email: user.email,
        role: user.role,
        accessToken: token.accessToken,
        //refreshToken: token.refreshToken,
        accessTokenExpires: Date.now() + token.expiresIn * 1000,
      };
    },
  }),
],
callbacks: {
  async jwt({ token, user }) {
    if (user) {
      return {
        accessToken: user.accessToken,
        //refreshToken: user.refreshToken,
        accessTokenExpires: Date.now() + 1000 * 60 * 60, // 1h
        user: {
          id: user.id,
          name: user.name,
          email: user.email,
          role: user.role
        },
      };
    }

    if (Date.now() < token.accessTokenExpires) {
      return token;
    }
  }
}
```

```

    return refreshAccessToken(token);
  },
  async session({ session, token }) {
    console.log("session in session method", session);
    console.log("token in session method", token);
    return {
      ...session,
      user: {
        ...session.user,
        id: token.user.id,
        name: token.user.name,
        email: token.user.email,
        accessToken: token.accessToken,
        //refreshToken: token.refreshToken,
      },
    };
  },
},
session: {
  strategy: 'jwt',
},
secret: process.env.NEXTAUTH_SECRET as string,
} satisfies NextAuthConfig;

//@ts-ignore
export const {handlers, auth, signIn, signOut} = NextAuth(authConfig);

```

Route api

Toutes les requêtes NextAuth passeront par cette route : `src/app/api/auth/[...nextauth]/route.tsx`

```

import {handlers} from "@/auth";
export const {GET, POST} = handlers;

```

Lib

Fichier utilitaire pour simplifier connexion et déconnexion dans `src/lib/actions.ts`:

```

'use server';
import {signIn, signOut} from "@/auth";

interface LoginFormValues {
  username: string;
  password: string;
  rememberMe?: boolean;
};
export const submitLogin = async (formData: LoginFormValues): Promise<any> => {

```

```
    await signIn('credentials', {...formData, redirectTo: '/', redirect: true});
  };

export const submitLogout = async () => {
  await signOut({redirect: true, redirectTo: '/logout'});
};
```

LoginForm

Exemple de composant pour le login :

```
'use client';
import {Button, Checkbox, Form, Input} from "antd";
import {submitLogin} from "@/lib/actions";

export default function SignInComponent(){
  const onFinish = async (values: any) => {
    await submitLogin(values);
  };

  const onFinishFailed = (errorInfo: any) => {
    console.log('Failed:', errorInfo);
  };
  return (
    <>
      <Form
        name="basic"
        labelCol={{ span: 8 }}
        wrapperCol={{ span: 16 }}
        style={{ maxWidth: 600 }}
        initialValues={{ remember: true }}
        onFinish={onFinish}
        onFinishFailed={onFinishFailed}
        autoComplete="off"
      >
        <Form.Item
          label="Username"
          name="username"
          rules={[{ required: true, message: 'Please input your username!'
        }}
        >
          <Input />
        </Form.Item>

        <Form.Item
          label="Password"
          name="password"
          rules={[{ required: true, message: 'Please input your password!'
        }}
        >
          <Input.Password />
        </Form.Item>
      </>
    )
  );
```

```
<Form.Item name="remember" valuePropName="checked" label={null}>
  <Checkbox>Remember me</Checkbox>
</Form.Item>

<Form.Item label={null}>
  <Button type="primary" htmlType="submit">
    Submit
  </Button>
</Form.Item>
</Form>
```

```
)
```

```
} </sxh>
```

From:
<http://slamwiki2.kobject.net/> - **SlamWiki 2.1**

Permanent link:
<http://slamwiki2.kobject.net/web/framework/nextjs/nextauth?rev=1742374176>

Last update: **2025/08/12 02:35**

