

Tests Spring

Dépendances pom.xml

```
<dependencies>
  ...
  <dependency>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-starter-test</artifactId>
    <scope>test</scope>
  </dependency>

  <dependency>
    <groupId>org.springframework.security</groupId>
    <artifactId>spring-security-test</artifactId>
    <scope>test</scope>
  </dependency>
<!--
https://mvnrepository.com/artifact/org.seleniumhq.selenium/selenium-java -->
  <dependency>
    <groupId>org.seleniumhq.selenium</groupId>
    <artifactId>selenium-java</artifactId>
    <scope>test</scope>
  </dependency>
<!--
https://mvnrepository.com/artifact/io.github.bonigarcia/webdrivermanager -->
  <dependency>
    <groupId>io.github.bonigarcia</groupId>
    <artifactId>webdrivermanager</artifactId>
    <version>5.3.1</version>
    <scope>test</scope>
  </dependency>
</dependencies>
```

@WebMvcTest

Tester un composant (Controller, service...)

Controller

```
@Controller
public class HelloController {
    @Autowired
    private HelloService helloService;

    @GetMapping("/hello")
```

```
public @ResponseBody String helloAction() {
    return helloService.getMessage();
}

@ModelAttribute("message")
public String getMessage() {
    return helloService.getMessage();
}

@GetMapping("/hello/view")
public String helloViewAction() {
    return "hello";
}

@GetMapping("/auth/hello")
public @ResponseBody String authHelloAction() {
    return helloService.getAuthMessage();
}

@GetMapping("/hello/js/{msg}")
public String helloWithJSAction(@PathVariable String msg) {
    return "helloJs";
}
}
```

Test

```
@WebMvcTest(HelloController.class)
@ContextConfiguration(classes = {WebSecurityConfig.class,
SpringTestsApplication.class})
class HelloControllerTest {

    @MockBean
    private HelloService helloService;

    @Autowired
    private MockMvc mockMvc;

    @Test
    void helloShouldReturnBonjour() throws Exception {
        // Given
        when(helloService.getMessage()).thenReturn("Bonjour");
        // When
        ResultActions results =
this.mockMvc.perform(MockMvcRequestBuilders.get("/hello"));
        // Then
        results.andExpect(MockMvcResultMatchers.status().isOk())
                .andExpect(content().string(containsString("Bonjour")));
    }

    @Test
    void helloViewShouldReturnBonjour() throws Exception {
        // Given
```

```
    when(helloService.getMessage()).thenReturn("Bonjour");
    // When
    ResultActions results =
this.mockMvc.perform(MockMvcRequestBuilders.get("/hello/view"));
    // Then
    results.andExpect(view().name("hello")).andExpect(model().attribute("message",
"Bonjour"))
        .andExpect(MockMvcResultMatchers.status().isOk())
        .andExpect(content().string(containsString("Bonjour")));
    }
}
```

Tests d'intégration

@SpringBootTest & @AutoConfigureMockMvc

```
@SpringBootTest
@AutoConfigureMockMvc
@AutoConfigureTestDatabase(replace = Replace.NONE)
class RestUserControllerTest {

    @Autowired
    private MockMvc mockMvc;

    @Autowired
    private UserService userService;

    private static User testUser;

    @BeforeEach
    public void setup() {
        testUser = userService.createUser("Bob", "Duke");
    }

    @AfterEach
    public void tearDown() {
        userService.deleteAll();
    }

    @Test
    void getAllShouldReturnAllUsers() throws Exception {
        this.mockMvc.perform(MockMvcRequestBuilders.get("/rest/users"))
            .andExpect(MockMvcResultMatchers.status().isOk())
            .andExpect(MockMvcResultMatchers.jsonPath("$.size()").value(1))
            .andExpect(MockMvcResultMatchers.jsonPath("$[0].firstname").value("Bob"))
            .andExpect(MockMvcResultMatchers.jsonPath("$[0].lastname").value("Duke"));
    }
}
```

Test sécurité

Authentification

Autorisations

```
@SpringBootTest
@AutoConfigureMockMvc
class SecureApplicationTests {

    @Autowired
    private MockMvc mockMvc;

    @Test
    @WithMockUser("admin")
    void authHelloWithAdminShouldReturnAdmin() throws Exception {
this.mockMvc.perform(get("/auth/hello")).andDo(print()).andExpect(status().isOk())
        .andExpect(content().string(containsString("admin")));
    }

    @Test
    @WithAnonymousUser
    void authHelloWithAnonymousUserShouldReturn401() throws Exception {
this.mockMvc.perform(get("/auth/hello")).andDo(print()).andExpect(status().isUnauthorized());
    }
}
```

Selenium tests

Tests du comportement côté client

Couverture

Intégration de **Jacoco** :

```
<build>
  <plugins>
    ...
    <plugin>
      <groupId>org.jacoco</groupId>
      <artifactId>jacoco-maven-plugin</artifactId>
```

```
<version>0.8.11</version>
<executions>
  <execution>
    <goals>
      <goal>prepare-agent</goal>
    </goals>
  </execution>
  <execution>
    <id>report</id>
    <phase>prepare-package</phase>
    <goals>
      <goal>report</goal>
    </goals>
  </execution>
</executions>
</plugin>
</plugins>
</build>
```

From:
<http://slamwiki2.kobject.net/> - **SlamWiki 2.1**

Permanent link:
<http://slamwiki2.kobject.net/web/framework/spring/tests?rev=1702859358>

Last update: **2023/12/18 01:29**

